Dry Weight (no options)2,060 lbsTongue Weight (no/vater)*301 lbsTongue Weight (w/water)*368 lbsGWWR3,500 lbsTorsion Axle Rating3,500 lbsOverall Length180° (15)Overall Uength95° (7' 11")Box Length (Exterior)142" (11' 10")Interior LQ Length80° (6' 8")Interior LQ Width69-1/2" (5' 9-1/2")Interior LQ Width69-1/2" (5' 9-1/2")Overall Height (w/Roof Rack)81-1/4" (6' 9-1/4")Overall Height (w/Roof Vent)80° (6' 8")Overall Height (w/Roof Vent)80° (6' 8")Overall Height (w/Roof Vent)74' (6' 2")Ground Clearance14-1/4"Roof Rack Capacity**400 lbsRear Receiver Capacity200 lbsCoupler2"Hitch Ball Height18-1/2"TiresS1235/75R15 LRCWheels15" x 6"Lug Patterin5 x 4-1/4"Spare TireYesElectric BrakesYes7Way PlugYesBatteryRequires AGM or Lithum Non-Vented BattFresh Water Tank27CallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Back65 lbs11,000 BTU200 lbsOVERD0000 BTURoof Back65 lbs11,000 BTU Roof Mount A/C10 lbs80 Y Size (BTU's)11,000 BTU80 Y Size (BTU's)30 lbs80 Y Size (BTU's)10 lbs80 Y Size (BTU's) <th>SPECIFICATIONS</th> <th>RŎG 12BH</th>	SPECIFICATIONS	RŎG 12BH
Tongue Weight (no/water)*301 lbsTongue Weight (w/water)*268 lbsGWR3,500 lbsGWR3,500 lbsOverall Length180° (15')Overall Width95° (7' 11')Box Length (Exterior)142° (11' 10")Interior LQ Length80° (6' 8")Interior LQ Width69 1/2° (5' 9-1/2")Interior LQ Width69 1/2° (5' 9-1/2")Interior LQ Height47-1/2" (3' 11-1/2")Overall Height (w/Roof Rack)81-1/4" (6' 9-1/4")Overall Height (w/Roof Rack)81-1/4" (6' 9-1/4")Overall Height (w/Roof Vent)74' (6' 2")Ground Clearance14-1/4"Roof Rack Capacity**400 lbsRear Receiver Capacity200 lbsCoupler2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYes7.Way PlugYesBatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27GatlonRef Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Top A/C (option)11,000 BTUOPTIONS90 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsOverland Packagen/a		
Tongue Weight (w/water)*268 lbsGWWR3,500 lbsTorsion Axle Rating3,500 lbsOverall Length180° (15')Overall Width95° (7' 11")Box Length (Exterior)142" (11' 10")Interior LQ Length80° (6' 8")Interior LQ Width69· 1/2" (5' 9· 1/2")Interior LQ Height47· 1/2" (3' 11- 1/2")Overall Height (w/Roof Rack)81· 1/4" (6' 9· 1/4")Overall Height (w/Roof Vent)74' (6' 2")Ground Clearance14· 1/4"Roof Rack Capacity**400 lbsRear Receiver Capacity200 lbsCoupler2"Hitch Ball Height18· 1/2"TiresST235/76R15 LRCWheels15" x6"Lug Pattern5 x 4· 1/4"Spare TireYesBatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27GaltonRef Size3.3 Cubic FeetFurnace Size (BTU's)18.000 BTURoof Back65 lbs11,000 BTU700 BTURoof Back65 lbs11,000 BTU Roof Mount A/C102 lbs82" Side and 4' 7" Rear Awning Combo30 lbsOVER AM31 lbs201 Us Libuing Mattery23 lbsOver AM44 lbs202 Us Libuing Mattery23 lbsOver Derive Mattery23 lbsOver Derive Mattery24 lbsOver Derive Mattery24 lbsOver Derive Mattery24 lbsOver Derive Mattery24 lbsOver Derive Mattery </td <td></td> <td></td>		
GWR 3,500 lbs Torsion Axle Rating 3,500 lbs Overall Length 180" (15') Overall Width 95" (7' 11") Box Length (Exterior) 142" (11' 10") Interior LQ Length 80" (6' 8") Interior LQ Width 69-1/2" (5' 9-1/2") Interior LQ Height 47-1/2" (3' 11-1/2") Overall Height (wRoof Rack) 81-1/4" (6' 9-1/4") Overall Height (wRoof Rack) 81-1/4" (6' 9-1/4") Overall Height (wRoof Vent) 74' (6' 2") Ground Clearance 14-1/4" Roof Rack Capacity* 400 lbs Rear Receiver Capacity 200 lbs Coupler 2" Hitch Ball Height 18-1/2" Tires ST235/75R15 LRC Wheels 15" 6" Lug Pattern 5 x 4-1/4" Spare Tire Yes Battery Requires AGM or Lithium Non-Vented Batt Fresh Water Tank 27Gallon Refer Size 3.3 Cubic Feet Furnace Size (BTU's) 18,000 BTU Roof Top A/C (Option) 11,000		
Torsion Axle Rating 3,500 lbs Overall Length 180" (15') Overall Width 95" (7" 11") Box Length (Exterior) 142" (11" 10") Interior LQ Length 80" (6'8") Interior LQ Height 47-1/2" (3" 11-1/2") Overall Height (w/Roof Rack) 81-1/4" (6'9-1/4") Overall Height (w/Roof Rack) 81-1/4" (6'9-1/4") Overall Height (w/Roof Vent) 74" (6'2") Ground Clearance 14-1/4" Roof Rack Capacity* 400 lbs Rear Receiver Capacity 200 lbs Coupler 2" Hitch Ball Height 18-1/2" Tires ST235/75R15 LRC Wheels 15" x 6" Lug Pattern 5 x 4-1/4" Spare Tire Yes Battery Requires AGM or Lithium Non-Vented Batt Fresh Water Tank 27Galton Refer Size 3.3 Cubic Feet Furnace Size (BTU's) 18,000 BTU Roof Top A/C (Option) 11,000 BTU Options 510 s Size Bards 100 lbs <td></td> <td></td>		
Overall Length 180" (15') Overall Width 95" (7' 11") Box Length (Exterior) 142" (11' 10") Interior LQ Length 80" (6' 8") Interior LQ Width 69-12" (5' 9-1/2") Interior LQ Height 47-1/2" (3' 11-1/2") Overall Height (wRoof Rack) 81-1/4" (6' 9-1/4") Overall Height (wRoof Rack) 81-1/4" (6' 9-1/4") Overall Height (wRoof Nent) 74' (6' 2") Ground Clearance 14-1/4" Roof Rack Capacity** 400 lbs Rear Receiver Capacity 200 lbs Coupler 2" Hitch Ball Height 18-1/2" Tires ST235/75R15 LRC Wheels 15" x 6" Lug Pattern 5 x 4-1/4" Spare Tire Yes Electric Brakes Yes Battery Requires AGM or Lithium Non-Vented Batt Fresh Water Tank 27Galton Refer Size 3.3 Cubic Feet Furnace Size (BTU's) 18.000 BTU Roof Top A/C (Option) 11.000 BTU OPTIONS 510		
Overall Width 95" (7' 11") Box Length (Exterior) 142" (11' 10") Interior LQ Length 80" (6' 8") Interior LQ Height 47-1/2" (3' 11-1/2") Interior LQ Height 47-1/2" (3' 11-1/2") Overall Height (w/Roof Rack) 81-1/4" (6' 9-1/4") Overall Height (w/Roof Vent) 74' (6' 2") Ground Clearance 14-1/4" Roof Rack Capacity** 400 lbs Rear Receiver Capacity 200 lbs Coupler 2" Hitch Ball Height 18-1/2" Tires ST235/75R15 LRC Wheels 15" x 6" Lug Pattern 5 x 4-1/4" Spare Tire Yes Electric Brakes Yes Pattern 27Gallon Refer Size 3.3 Cubic Feet Furnace Size (BTU's) 18,000 BTU Roof Top A/C (Option) 11,000 BTU OPTIONS 110 lbs Sourd A 4' "Rear Awning Combo 30 lbs 10/20 LD 5 512 Size and 4' 7" Rear Awning Combo 30 lbs <td< td=""><td>-</td><td></td></td<>	-	
Box Length (Exterior)142" (11' 10")Interior LQ Length80" (6' 8")Interior LQ Width69-1/2" (5' 9-1/2")Interior LQ Width81-1/4" (6' 9-1/4")Overall Height (w/Roof Rack)81-1/4" (6' 9-1/4")Overall Height (w/Roof Vent)74' (6' 2")Ground Clearance14-1/4"Roof Rack Capacity**400 lbsRear Receiver Capacity200 lbsCoupler2"Hitch Ball Height18-1/2"TiresST225/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesBatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Rack65 lbs11,000 BTU70 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8' 2'' Side and 4'''' Rear Awning Combo30 lbsOVER Tankes23 lbs22" 12V TV W Swivel Mount & Antenna14 lbs22'' 12V Lithium Battery23 lbsPower Up Package49 lbsOver Land Package40 lbsOver Land Package40 lbs	-	
Interior LQ Length80" (6' 8")Interior LQ Width69-1/2" (5' 9-1/2")Interior LQ Height47-1/2" (3' 11-1/2")Overall Height (w/Roof Rack)81-1/4" (6' 9-1/4")Overall Height (w/Roof Vent)74' (6' 2")Ground Clearance14-1/4"Roof Rack Capacity**400 lbsRear Receiver Capacity200 lbsCoupler2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesBatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Rack65 lbs11,000 BTU0PTIONSSurvival Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8'2" Side and 4'7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs22" 12V TV W Swivel Mount & Antenna14 lbs22V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		. ,
Interior LQ Width 69-1/2" (5'9-1/2") Interior LQ Height 47-1/2" (3' 11-1/2") Overall Height (w/Roof Rack) 81-1/4" (6' 9-1/4") Overall Height (w/A/C) 80" (6' 8") Overall Height (w/A/C) 80" (6' 8") Overall Height (w/Roof Vent) 74' (6' 2") Ground Clearance 14-1/4" Roof Rack Capacity* 400 lbs Rear Receiver Capacity 200 lbs Coupler 2" Hitch Ball Height 18-1/2" Tires ST235/75R15 LRC Wheels 15" x 6" Lug Pattern 5 x 4-1/4" Spare Tire Yes Electric Brakes Yes Pattern 5 x 4-1/4" Spare Tire 3.3 Cubic Feet Fresh Water Tank 27Galton Refer Size 3.3 Cubic Feet Furnace Size (BTU's) 18,000 BTU Roof Rack 65 lbs 11,000 BTU Roof Mount A/C 102 lbs 8'2" Side and 4'7" Rear Awning Combo 30 lbs OVS 270 Degree Awning 33 lbs		
Interior LQ Height47-1/2" (3' 11-1/2")Overall Height (w/Roof Rack)81-1/4" (6' 9-1/4")Overall Height (w/Roof Vent)74' (6' 2")Ground Clearance14-1/4"Roof Rack Capacity**400 lbsRear Receiver Capacity200 lbsCoupler2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x6"Lug Pattern5 x4-1/4"Spare TireYesElectric Brakes987-Way PlugYesBatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Rack65 lbs11.000 BTU Roof Mount A/C102 lbs8'2 "Side and 4' 7" Rear Awning Combo30 lbsOVE S23' 12V TV w/ Swivel Mount & Antenna2'' 14 lbs12V TV w/ Swivel Mount & Antenna2'' 14 lbs12V Lithium BatteryPower Up Package49 lbsOverland Packagen/a	-	
Overall Height (w/Roof Rack)81-1/4" (6' 9-1/4")Overall Height (w/A/C)80" (6' 8")Overall Height (w/Roof Vent)74' (6' 2")Ground Clearance14-1/4"Roof Rack Capacity**400 lbsRear Receiver Capacity200 lbsCoupler2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYesElectric BrakesYesBatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27 GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Top A/C (Option)11,000 BTUOPTIONS110 lbsSnof Rack65 lbs110,000 BTU Roof Mount A/C102 lbs8'2" Side and 4'7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs23" 12V TV w/ Swivel Mount & Antenna14 lbsOverland Package49 lbsOverland Package49 lbs		
Overall Height (w/A/C)80" (6' 8")Overall Height (w/Roof Vent)74' (6' 2")Ground Clearance14-1/4"Roof Rack Capacity**400 lbsRear Receiver Capacity200 lbsCoupler2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYesPatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Top A/C (Option)11,000 BTUOPTIONS30 lbsSurvial Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		
Overall Height (w/Roof Vent)74' (6' 2")Ground Clearance14-1/4"Roof Rack Capacity**400 lbsRear Receiver Capacity200 lbsCoupler2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYesAtter Tank27GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Tack65 lbs11,000 BTU Roof Mount A/C102 lbs8'2" Side and 4'7" Rear Awning Combo30 lbs0VS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		
Ground Clearance14-1/4"Roof Rack Capacity**400 lbsRear Receiver Capacity200 lbsCoupler2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYesPturgeYesBatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Top A/C (Option)11,000 BTUOPTIONS5Survival Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8'2" Side and 4'7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a	,	. ,
Roof Rack Capacity**400 lbsRear Receiver Capacity200 lbsCoupler2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYesZ-Way PlugYesBatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8'2" Side and 4' 7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		. ,
Rear Receiver Capacity200 lbsCoupler2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYes7-Way PlugYesBatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Top A/C (Option)11,000 BTUOPTIONS102 lbsSurvival Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		
Coupler2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYesZ'Way PlugYesBatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27 GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Top A/C (Option)11,000 BTUOPTIONSSurvival SeriesSurvival Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8'2" Side and 4' 7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		
Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYes7-Way PlugYesBatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Top A/C (Option)11,000 BTU OPTIONS 900 BTUSurvival Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8'2" Side and 4'7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		
TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYesZ-Way PlugYesBatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Top A/C (Option)11,000 BTUOPTIONS110 lbsSurvival Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8'2" Side and 4' 7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		
Wheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYes7-Way PlugYesBatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Top A/C (Option)11,000 BTUOPTIONSSurvival SeriesSurvival Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8' 2" Side and 4' 7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		
Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYes7-Way PlugYesBatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Top A/C (Option)11,000 BTUOPTIONSSurvival Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8' 2" Side and 4' 7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		
Spare TireYesSpare TireYesElectric BrakesYes7-Way PlugYesBatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Top A/C (Option)11,000 BTUOPTIONSSurvival Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8'2" Side and 4' 7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		
Electric BrakesYes7-Way PlugYesBatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Top A/C (Option)11,000 BTUOPTIONSSurvival Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8' 2" Side and 4' 7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		
BatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Top A/C (Option)11,000 BTUOPTIONSSurvival Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8' 2'' Side and 4' 7'' Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32'' 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a	· ·	
BatteryRequires AGM or Lithium Non-Vented BattFresh Water Tank27GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Top A/C (Option)11,000 BTUOPTIONSSurvival Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8' 2'' Side and 4' 7'' Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32'' 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		
Fresh Water Tank27GallonRefer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Top A/C (Option)11,000 BTUOPTIONSSurvival Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8' 2" Side and 4' 7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		Requires AGM or Lithium Non-Vented Batt
Refer Size3.3 Cubic FeetFurnace Size (BTU's)18,000 BTURoof Top A/C (Option)11,000 BTUOPTIONSSurvival Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8' 2" Side and 4' 7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a	· · · ·	27Gallon
Furnace Size (BTU's)18,000 BTURoof Top A/C (Option)11,000 BTUOPTIONSSurvival Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8' 2" Side and 4' 7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		3.3 Cubic Feet
Roof Top A/C (Option)11,000 BTUOPTIONSSurvival Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8' 2'' Side and 4' 7'' Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32'' 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a	Furnace Size (BTU's)	
OPTIONSSurvival Series110 lbsRoof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8' 2" Side and 4' 7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		
Roof Rack65 lbs11,000 BTU Roof Mount A/C102 lbs8' 2" Side and 4' 7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		
11,000 BTU Roof Mount A/C102 lbs8' 2" Side and 4' 7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a	Survival Series	110 lbs
8' 2" Side and 4' 7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a	Roof Rack	65 lbs
8' 2" Side and 4' 7" Rear Awning Combo30 lbsOVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a	11,000 BTU Roof Mount A/C	102 lbs
OVS 270 Degree Awning63 lbs32" 12V TV w/ Swivel Mount & Antenna14 lbs12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		30 lbs
12V Lithium Battery23 lbsPower Up Package49 lbsOverland Packagen/a		63 lbs
Power Up Package 49 lbs Overland Package n/a	32" 12V TV w/ Swivel Mount & Antenna	14 lbs
Overland Package n/a	12V Lithium Battery	23 lbs
	Power Up Package	49 lbs
Overland Package+**** 125 lbs	Overland Package	n/a
	Overland Package+****	125 lbs

*Tongue Weight includes the following options (Roof Rack, A/C, & Awning Package)

Roof Rack rated at 100 lbs (45 kg) per crossbar – Dynamic Rating – Rolling Down Road *You <u>cannot</u> use a standard wet cell deep cycle battery

****Overland Package+ Includes Heavy-Duty Fenders