| SPECIFICATIONS | RŎG 14TH1 | RŎG 14TH2 |
|--|--|-----------------------|
| Dry Weight (no options) | 2,368 lbs | 2437 lbs |
| Tongue Weight (no/water)* | 567 lbs | 567 lbs |
| Tongue Weight (w/water)* | 536 lbs | 536 lbs |
| GVWR | 4,400 lbs | 4,400 lbs |
| Torsion Axle Rating | 4,000 lbs | 4,000 lbs |
| Overall Length | 198-1/4" (16' 6-1/4") | 198-1/4" (16' 6-1/4") |
| Overall Width | 95" (7' 11") | 95" (7' 11") |
| Box Length (Exterior) | 165-1/2" (13' 9-1/2") | 165-1/2" (13' 9-1/2") |
| Interior Floor Length | 136" (11' 4") | 136" (11' 4") |
| Interior LQ Width | 69-1/2" (5' 9-1/2") | 69-1/2" (5' 9-1/2") |
| Interior LQ Height | 73" (6' 1") | 73" (6' 1") |
| Interior LQ Height @ A/C | 69-3/4" | 69-3/4" |
| Ramp Door Opening | 70-1/2" x 64" | 70-1/2" x 64" |
| Ramp Door Platform | 70" x 63" | 70" x 63" |
| Ramp Door Capacity | 2,500 lbs | 2,500 lbs |
| Tip-Out Size | 77" x 44" R/S | 77" x 44" C/S |
| Tip-Out Capacity | 1,100 lbs. | 1,100 lbs. |
| Overall Height (w/A/C) | 108-1/2" (9' 1/2") | 108-1/2" (9' 1/2") |
| Overall Height (w/Roof Vent) | 102-1/2" (8' 6-1/2") | 102-1/2" (8' 6-1/2") |
| Ground Clearance | 11-1/8" | 11-1/8" |
| Roof Rack Capacity** | 400 lbs | 400 lbs |
| Rear Receiver Capacity | 200 lbs | 200 lbs |
| Coupler | 2-5/16" | 2-5/16" |
| Hitch Ball Height | 17-1/2" | 17-1/2" |
| Tires | ST235/75R15 LRC | ST235/75R15 LRC |
| Wheels | 15" x 6" | 15" x 6" |
| Lug Pattern | 5 x 4-1/4" | 5 x 4-1/4" |
| Spare Tire | Yes | Yes |
| Electric Brakes | Yes | Yes |
| 7-Way Plug | Yes | Yes |
| Battery | Requires AGM or Lithium Non-Vented Batt Compartment*** | |
| Fresh Water Tank | 26 Gallons | 26 Gallons |
| Refer Size | 3.3 Cubic Feet | 3.3 Cubic Feet |
| Furnace Size (BTU's) | 18,000 BTU | 18,000 BTU |
| Roof Top A/C (Option) | 11,000 BTU | 11,000 BTU |
| OPTIONS | | |
| Survival Series | 110 lbs | 110 lbs |
| Roof Rack | 65 lbs | 65 lbs |
| 11,000 BTU Roof Mount A/C | 102 lbs | 102 lbs |
| 8' 2" Side and 4' 7" Rear Awning Combo | 30 lbs | 30 lbs |
| OVS 270 Degree Awning | 63 lbs | 63 lbs |
| 12V Lithium Battery | 23 lbs | 23 lbs |
| Power Up Package | 49 lbs | 49 lbs |
| Overland Package | n/a | n/a |
| Overland Package+*** | 125 lbs | 125 lbs |

^{*}Tongue Weight includes the following options (Roof Rack, A/C, & Awning Package)

^{**}Roof Rack rated at 100 lbs (45 kg) per crossbar – Dynamic Rating – Rolling Down Road ***You *cannot* use a standard wet cell deep cycle battery

^{****}Overland Package+ Includes Heavy-Duty Fenders