SPECIFICATIONS	RŎG 16RB
Dry Weight (no options)	2,900 lbs
Tongue Weight (no/water)*	452 lbs
GVWR	4,400 lbs
Torsion Axle Rating	4,000 lbs
Overall Length	233" (19' 5")
Overall Width	95" (7' 11")
Box Length (Exterior)	190" (15' 10")
Interior Floor Length	81" (6' 9")
Interior LQ Width	69-1/2" (5' 9-1/2")
Interior LQ Height	73" (6' 1")
Interior Bunk Length	80" (6' 8")
Interior Bunk Height	48" (4')
Dinette Bunk Dimensions	69" x 32"
Overall Height (w/Roof Rack)	109-3/4" (9' 1-3/4")
Overall Height (w/A/C)	108-1/2" (9' 1/2")
Overall Height (w/Roof Vent)	102-1/2" (8' 6-1/2")
Ground Clearance	11-1/8"
Roof Rack Capacity**	500 lbs
Rear Receiver Capacity	200 lbs
Coupler	2-5/16"
Hitch Ball Height	17-1/2"
Tires	ST235/75R15 LRC
Wheels	15" x 6"
Lug Pattern	5 x 4-1/4"
Spare Tire	Yes
Electric Brakes	Yes
7-Way Plug	Yes
Battery	Requires AGM or Lithium Non-Vented
	Batt Compartment***
Fresh Water Tank	54 Gallons
Refer Size - Inside	4.5 Cubic Feet
Refer Size - Outside	1.7 Cubic Feet
Furnace Size (BTU's)	18,000 BTU
Roof Top A/C (Option)	11,000 BTU
OPTIONS	
Survival Series	110 lbs
Roof Rack	65 lbs
11,000 BTU Roof Mount A/C	102 lbs
10' Thule Awning	44 lbs
32" 12V TV w/Swivel Mount and Antenna	14 lbs
12V Lithium Battery	23 lbs
Power Up Package	49 lbs
Overland Package	n/a
Overland Package+***	125 lbs

^{*}Tongue Weight includes the following options (Roof Rack, A/C, & Awning Package)

**Roof Rack rated at 100 lbs (45 kg) per crossbar – Dynamic Rating – Rolling Down Road

***You <u>cannot</u> use a standard wet cell deep cycle battery

^{****}Overland Package+ Includes Heavy-Duty Fenders