Dry Weight (no options) 1,585 lbs Tongue Weight (no/water)* 291 lbs Tongue Weight (w/water)* 291 lbs GWWR 3,500 lbs Gvwrall Length 164-1/2" (13' 8-1/2") Overall Length 164-1/2" (13' 8-1/2") Overall Length 164-1/2" (13' 8-1/2") Overall Width 95" (7' 11") Box Length (Exterior) 118" (9' 10") Interior LQ Width 70" (5' 10") Interior Q Height 70-1/2" (5' 10-1/2") Interior Q Height (wRoof Rack) 104" (8' 8") Overall Height (wRoof Rack) 104" (8' 8") Overall Height (wRoof Vent) 102-1/2" (6' 10-1/2") Roof Rack Capacity** 200 lbs Coupler 2" Hitch Ball Height 18-1/2" Tires ST35/7815 LRC Wheels 15" x 6" Lug Pattern 5 x 4-1/4" Spare Tire Yes Electric Brakes Yes Battery Requires AGM or Lithium Non-Vented Batt Compartment*** Fresh Water Tank 21 Galton Refer	SPECIFICATIONS	VENŪ 10KB
Tongue Weight (no/water)* 291 lbs Tongue Weight (w/water)* 257 lbs GVWR 3,500 lbs Torsion Axle Rating 3,500 lbs Overall Length 164-1/2" (13' 8-1/2") Overall Width 95" (7' 11") Box Length (Exterior) 118" (9' 10") Interior LQ Width 70" (5' 10") Interior LQ Height 70-1/2" (5' 10-1/2") Interior LQ Height 80" (6' 8") Overall Height (w/Roof Rack) 104" (8' 8") Overall Height (w/Roof Vent) 102-1/2" (8' 6-1/2") Roof Rack Capacity** 200 lbs Coupler 2" Hitch Ball Height 18-1/2" Tires ST235/75R15 LRC Wheels 15" x 6" Lug Pattern 5 x 4-1/4" Spare Tire Yes Electric Brakes Yes Plug Yes Battery Requires AGM or Lithium Non-Vented Batt Compartment*** Fresh Water Tank 21 Galon Refer Size 3.3 Cubic Feet A/C 41 das		
Tongue Weight (w/water)* 257 lbs GVWR 3,500 lbs Torsion Axle Rating 3,500 lbs Overall Length 164-1/2" (13'8-1/2") Overall Width 95" (7' 11") Box Length (Exterior) 118" (9' 10") Interior LQ Width 70" (5' 10") Overall Height (w/Roof Rack) 104" (8' 8") Overall Height (w/Roof Vent) 102-1/2" (8' 6-3/4") Overall Height (w/Roof Vent) 102-1/2" (8' 6-1/2") Roof Rack Capacity** 200 lbs Coupler 2" Hitch Ball Height 18-1/2" Tires ST235/75R15 LRC Wheels 15" x 6" Lg Pattern		•
GWWR 3,500 lbs Torsion Axie Rating 3,500 lbs Overall Length 164-1/2" (13' 8-1/2") Overall Width 95" (7' 11") Box Length (Exterior) 118" (9' 10") Interior LQ Width 70" (5' 10") Interior LQ Height 70-1/2" (5' 10-1/2") Interior Bunk Length 80" (6' 8") Overall Height (w/Roof Rack) 104" (8' 8") Overall Height (w/Roof Vent) 102-1/2" (8' 6-3/4") Overall Height (w/Roof Vent) 102-1/2" Roof Rack Capacity** 200 lbs Coupler 2" Hitch Ball Height 18-1/2" Tires St235/75R15 LRC Wheels 15" x 6" Lug Pattern 5 x 4-1/4" Spare Tire Yes Battery Compartm		
Torsion Axle Rating3,500 lbsOverall Length164-1/2" (13'8-1/2")Overall Width95" (7' 11")Box Length (Exterior)118" (9' 10")Interior LQ Width70" (5' 10")Interior LQ Height70-1/2" (5' 10-1/2")Interior LQ Height80" (6' 8")Overall Height (w/Roof Rack)104" (8' 8")Overall Height (w/Roof Vent)102-3/4" (8' 6-3/4")Overall Height (w/Roof Vent)102-1/2" (8' 6-1/2")Roof Rack Capacity**200 lbsCoupler2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesBatteryRequires AGM or Lithium Non-Vented Batt Compartment***Fresh Water Tank21 GaltonRefer Size3.3 Cubic FeetA/C WHeat Pump (Option)8K BTU Basement A/C w/ 8K BTU Heat PumpOPTIONS23 lbs24 UL Heat Pump23 lbs25 Ubs32" 12V TW/Locking Mount20 Libs25 lbs21 1b25 lbs22 1a Vew Ports11b		
Overall Length 164-1/2" (13' 8-1/2") Overall Width 95" (7' 11") Box Length (Exterior) 118" (9' 10") Interior LQ Width 70" (5' 10") Interior LQ Height 70-1/2" (5' 10-1/2") Interior Bunk Length 80" (6' 8") Overall Height (w/Roof Rack) 104" (8' 8") Overall Height (w/Roof Rack) 102-3/4" (8' 6-3/4") Overall Height (w/Roof Vent) 102-1/2" (8' 6-3/4")<		,
Overall Width 95" (7' 11") Box Length (Exterior) 118" (9' 10") Interior LQ Width 70" (5' 10") Interior LQ Height 70-1/2" (5' 10-1/2") Interior Bunk Length 80" (6' 8") Overall Height (w/Roof Rack) 104" (8' 8") Overall Height (w/Roof Vent) 102-3/4" (8' 6-3/4") Overall Height (w/Roof Vent) 102-3/4" (8' 6-3/4") Overall Height (w/Roof Vent) 102-1/2" (8' 6-1/2") Roof Rack Capacity** 200 lbs Coupler 2" Hitch Ball Height 18-1/2" Tires ST235/75R15 LRC Wheels 15" x 6" Lug Pattern 5 x 4-1/4" Spare Tire Yes Electric Brakes Yes Pattern S x 4-1/4" Spare Tire Yes Battery Compartment*** Fresh Water Tank 21 Gallon Refer Size 3.3 Cubic Feet A/C W/ Heat Pump (Option) 8K BTU Basement A/C w/ 8K BTU Heat Pump OPTIONS 31 lbs A/C 61 lbs </td <td></td> <td></td>		
Box Length (Exterior) 118" (9' 10") Interior LQ Width 70" (5' 10") Interior LQ Height 70-1/2" (5' 10-1/2") Interior Bunk Length 80" (6' 8") Overall Height (wRoof Rack) 104" (8' 8") Overall Height (wRoof Vent) 102-3/4" (8' 6-3/4") Overall Height (wRoof Vent) 102-1/2" (8' 6-1/2") Roof Rack Capacity** 200 lbs Coupler 2" Hitch Ball Height 18-1/2" Tires ST235/75R15 LRC Wheels 15" x 6" Lug Pattern 5 x 4-1/4" Spare Tire Yes Electric Brakes Yes Pattern 5 x 4-1/4" Spare Tire Yes Battery Requires AGM or Lithium Non-Vented Batt Compartment*** Fresh Water Tank 21 Gallon Refer Size 3.3 Cubic Feet A/C w/ Heat Pump (Option) 8K BTU Basement A/C w/ 8K BTU Heat Pump OPTIONS 13 lbs I2V Lithium Battery 23 lbs 24 UD Fenders 25 lbs 232" 12V TW wLocking Mount	5	· · · · ·
Interior LQ Width 70" (5' 10") Interior LQ Height 70-1/2" (5' 10-1/2") Interior Bunk Length 80" (6' 8") Overall Height (w/Roof Rack) 104" (8' 8") Overall Height (w/ACO) 102-3/4" (8' 6-3/4") Overall Height (w/ACO) 102-1/2" (8' 6-1/2") Roof Rack Capacity** 200 lbs Coupler 2" Hitch Ball Height 18-1/2" Tires ST235/75R15 LRC Wheels 15" x 6" Lug Pattern 5 x 4-1/4" Spare Tire Yes Electric Brakes Yes Battery Requires AGM or Lithium Non-Vented Batt Compartment*** Fresh Water Tank Refer Size 3.3 Cubic Feet A/C w/ Heat Pump (Option) 8K BTU Basement A/C w/ 8K BTU Heat Pump OPTIONS 33 lbs A/C 61 lbs Front O/H Cabinet 13 lbs 12V Lithium Battery 23 lbs 21 HD Fenders 25 lbs 32" 12V TV w/Locking Mount 12 lbs (2) 12V Power Ports 1 lb		· · · · ·
Interior LQ Height 70-1/2" (5 '10-1/2") Interior Bunk Length 80" (6' 8") Overall Height (w/Roof Rack) 104" (8' 8") Overall Height (w/Roof Vent) 102-3/4" (8' 6-3/4") Overall Height (w/Roof Vent) 102-1/2' (8' 6-1/2") Roof Rack Capacity** 200 lbs Coupler 2" Hitch Ball Height 18-1/2" Tires ST235/75R15 LRC Wheels 15" x 6" Lug Pattern 5 x 4-1/4" Spare Tire Yes Electric Brakes Yes Battery Requires AGM or Lithium Non-Vented Batt Compartment*** Fresh Water Tank 21 Galton Refer Size 3.3 Cubic Feet A/C w/ Heat Pump (Option) 8K BTU Basement A/C w/ 8K BTU Heat Pump OPTIONS 33 lbs A/C 61 lbs Front O/H Cabinet 13 lbs 12V Lithium Battery 23 lbs 21 HD Fenders 25 lbs 23" 12V TV w/Locking Mount 12 lbs (2) 12V Power Ports 1 lb Rear Awning and Bracket		· · · ·
Interior Bunk Length80" (6' 8")Overall Height (w/Roof Rack)104" (8' 8")Overall Height (w/A/C)102-3/4" (8' 6-3/4")Overall Height (w/Roof Vent)102-1/2' (8' 6-1/2")Roof Rack Capacity**200 lbsCoupler2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYesPatteryRequires AGM or Lithium Non-Vented Batt Compartment***Fresh Water Tank21 GallonRefer Size3.3 Cubic FeetA/C w/ Heat Pump (Option)8K BTU Basement A/C w/ 8K BTU Heat PumpOPTIONS31 lbsRoof Rack33 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs21 HD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports1 lbRear Awning and Bracket17 lbs		
Overall Height (w/Roof Rack)104" (8' 8")Overall Height (w/A/C)102-3/4" (8' 6-3/4")Overall Height (w/Roof Vent)102-1/2' (8' 6-1/2")Roof Rack Capacity**200 lbsCoupler2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYes7-Way PlugYesBatteryRequires AGM or Lithium Non-Vented Batt Compartment***Fresh Water Tank21 GallonRefer Size3.3 Cubic FeetA/C w/ Heat Pump (Option)8K BTU Basement A/C w/ 8K BTU Heat PumpOPTIONS31 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs21 Baltery23 lbs21 Ly Tv w/Locking Mount12 lbs12 V Lithium Battery10 lbs12 V Lithium Battery11 lb12 V Lithium Battery12 lbs12 V Dower Ports1 lbRear Awning and Bracket17 lbs		, , , , , , , , , , , , , , , , , , ,
Overall Height (w/A/C)102-3/4" (8' 6-3/4")Overall Height (w/Roof Vent)102-1/2' (8' 6-1/2")Roof Rack Capacity**200 lbsCoupler2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYesBatteryRequires AGM or Lithium Non-Vented Batt Compartment***Fresh Water Tank21 GallonRefer Size3.3 Cubic FeetA/C w/ Heat Pump (Option)8K BTU Basement A/C w/ 8K BTU Heat PumpOPTIONS31 lbsRoof Rack33 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs23 lbs25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports1 lbRear Awning and Bracket17 lbs	-	. ,
Overall Height (w/Roof Vent)102-1/2' (8' 6-1/2'')Roof Rack Capacity**200 lbsCoupler2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYesBatteryRequires AGM or Lithium Non-Vented Batt Compartment***Fresh Water Tank21 GallonRefer Size3.3 Cubic FeetA/C w/ Heat Pump (Option)8K BTU Basement A/C w/ 8K BTU Heat PumpOPTIONS33 lbsRoof Rack33 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs24 HD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports1 lbRear Awning and Bracket17 lbs		
Roof Rack Capacity**200 lbsCoupler2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYesBatteryRequires AGM or Lithium Non-Vented Batt Compartment***Fresh Water Tank21 GallonRefer Size3.3 Cubic FeetA/C w/ Heat Pump (Option)8K BTU Basement A/C w/ 8K BTU Heat PumpOPTIONS33 lbsRoof Rack33 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs23 lbs25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports1 lbRear Awning and Bracket17 lbs		
Coupler2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYes7-Way PlugYesBatteryRequires AGM or Lithium Non-Vented Batt Compartment***Fresh Water Tank21 GallonRefer Size3.3 Cubic FeetA/C w/ Heat Pump (Option)8K BTU Basement A/C w/ 8K BTU Heat PumpOPTIONS7000 RackRoof Rack33 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs24 DD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports11bRear Awning and Bracket17 lbs		· · ·
Hitch Ball Height18-1/2"Hitch Ball Height18-1/2"TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYes7-Way PlugYesBatteryRequires AGM or Lithium Non-Vented Batt Compartment***Fresh Water Tank21 GallonRefer Size3.3 Cubic FeetA/C w/ Heat Pump (Option)8K BTU Basement A/C w/ 8K BTU Heat PumpOPTIONSTRoof Rack33 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs24 DD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports11bRear Awning and Bracket17 lbs		
TiresST235/75R15 LRCWheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYes7-Way PlugYesBatteryRequires AGM or Lithium Non-Vented Batt Compartment***Fresh Water Tank21 GallonRefer Size3.3 Cubic FeetA/C w/ Heat Pump (Option)8K BTU Basement A/C w/ 8K BTU Heat PumpOPTIONSRoof Rack33 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs25 lbs32" 12V TV w/Locking Mount(2) 12V Power Ports1 lbRear Awning and Bracket17 lbs	•	
Wheels15" x 6"Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYes7-Way PlugYesBatteryRequires AGM or Lithium Non-Vented Batt Compartment***Fresh Water Tank21 GallonRefer Size3.3 Cubic FeetA/C w/ Heat Pump (Option)8K BTU Basement A/C w/ 8K BTU Heat PumpOPTIONS9Roof Rack33 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs2 HD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports1 lbRear Awning and Bracket17 lbs		
Lug Pattern5 x 4-1/4"Spare TireYesElectric BrakesYes7-Way PlugYesBatteryRequires AGM or Lithium Non-Vented Batt Compartment***Fresh Water Tank21 GallonRefer Size3.3 Cubic FeetA/C w/ Heat Pump (Option)8K BTU Basement A/C w/ 8K BTU Heat PumpOPTIONS9Roof Rack33 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs24 HD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports1 lbRear Awning and Bracket17 lbs		
Spare TireYesElectric BrakesYes7-Way PlugYesBatteryRequires AGM or Lithium Non-Vented Batt Compartment***Fresh Water Tank21 GallonRefer Size3.3 Cubic FeetA/C w/ Heat Pump (Option)8K BTU Basement A/C w/ 8K BTU Heat PumpOPTIONS9Roof Rack33 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs2 HD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports11 lbRear Awning and Bracket17 lbs		
Electric BrakesYes7-Way PlugYesBatteryRequires AGM or Lithium Non-Vented Batt Compartment***Fresh Water Tank21 GallonRefer Size3.3 Cubic FeetA/C w/ Heat Pump (Option)8K BTU Basement A/C w/ 8K BTU Heat PumpOPTIONS0Roof Rack33 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs2 HD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports11 lbRear Awning and Bracket17 lbs		
7-Way PlugYesBatteryRequires AGM or Lithium Non-Vented Batt Compartment***Fresh Water Tank21 GallonRefer Size3.3 Cubic FeetA/C w/ Heat Pump (Option)8K BTU Basement A/C w/ 8K BTU Heat PumpOPTIONS9KRoof Rack33 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs2 HD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports11 lbRear Awning and Bracket17 lbs	Electric Brakes	
Compartment***Fresh Water Tank21 GallonRefer Size3.3 Cubic FeetA/C w/ Heat Pump (Option)8K BTU Basement A/C w/ 8K BTU Heat PumpOPTIONSRoof Rack33 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs2 HD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports11bRear Awning and Bracket17 lbs	7-Way Plug	
Compartment***Fresh Water Tank21 GallonRefer Size3.3 Cubic FeetA/C w/ Heat Pump (Option)8K BTU Basement A/C w/ 8K BTU Heat PumpOPTIONS9Roof Rack33 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs2 HD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports11bRear Awning and Bracket17 lbs	Battery	Requires AGM or Lithium Non-Vented Batt
Fresh Water Tank21 GallonRefer Size3.3 Cubic FeetA/C w/ Heat Pump (Option)8K BTU Basement A/C w/ 8K BTU Heat PumpOPTIONS8K BTU Basement A/C w/ 8K BTU Heat PumpRoof Rack33 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs2 HD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports1 lbRear Awning and Bracket17 lbs		Compartment***
A/C w/ Heat Pump (Option)&K BTU Basement A/C w/ &K BTU Heat PumpOPTIONSRoof Rack33 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs2 HD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports1 lbRear Awning and Bracket17 lbs	Fresh Water Tank	
OPTIONSRoof Rack33 lbsA/C61 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs2 HD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports1 lbRear Awning and Bracket17 lbs	Refer Size	3.3 Cubic Feet
Roof Rack33 lbsA/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs2 HD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports1 lbRear Awning and Bracket17 lbs	A/C w/ Heat Pump (Option)	8K BTU Basement A/C w/ 8K BTU Heat Pump
A/C61 lbsFront O/H Cabinet13 lbs12V Lithium Battery23 lbs2 HD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports1 lbRear Awning and Bracket17 lbs	OPTIONS	
Front O/H Cabinet13 lbs12V Lithium Battery23 lbs2 HD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports1 lbRear Awning and Bracket17 lbs	Roof Rack	33 lbs
12V Lithium Battery23 lbs2 HD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports1 lbRear Awning and Bracket17 lbs	A/C	61 lbs
2 HD Fenders25 lbs32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports1 lbRear Awning and Bracket17 lbs	Front O/H Cabinet	13 lbs
32" 12V TV w/Locking Mount12 lbs(2) 12V Power Ports1 lbRear Awning and Bracket17 lbs	12V Lithium Battery	23 lbs
(2) 12V Power Ports 1 lb Rear Awning and Bracket 17 lbs	2 HD Fenders	25 lbs
Rear Awning and Bracket 17 lbs	32" 12V TV w/Locking Mount	12 lbs
-	(2) 12V Power Ports	1 lb
3.3 Cubic Foot Refer 23 lbs	Rear Awning and Bracket	17 lbs
	3.3 Cubic Foot Refer	23 lbs

*Tongue Weight includes the following options (Roof Rack, A/C, & Awning Package)

Roof Rack rated at 100 lbs (45 kg) per crossbar – Dynamic Rating – Rolling Down Road *You <u>cannot</u> use a standard wet cell deep cycle battery

****Overland Package+ Includes Heavy-Duty Fenders