



| Specifications | 10KB |
|----------------------------------|--------------------------------|
| Dry Weight (No Options) | 1,585 lbs |
| Tongue Weight (No Water)* | 291 lbs. |
| Tongue Weight (w/Water)* | 257 lbs. |
| GVWR | 3,500 lbs. |
| Torsion Axle Rating | 3,500 lbs. |
| Overall Length | 164-1/2" (13' 8-1/2") |
| Overall Width | 95" (7' 11") |
| Box Length (Exterior) | 118" (9' 10") |
| Interior LQ Width | 70" (5' 10") |
| Interior LQ Height | 70-1/2" (5' 10-1/2") |
| Interior Bunk Length | 80" (6' 8") |
| Overall Height w/Roof Rack | 104" (8' 8") |
| Overall Height w/A/C | 102-1/2" (8' 6-3/4") |
| Overall Height w/Roof Vent | 102-1/2" (8' 6-3/4") |
| Roof Rack Capacity** | 200 lbs. |
| Rear Receiver Capacity | N/A |
| Ground Clearance | 13-1/2" |
| Coupler | 2" |
| Hitch Ball Height | 18-1/2" |
| Tires | ST235/75R15 LRC |
| Wheels | 15" X 6" |
| Lug Pattern | 5 X 4-1/4" |
| Spare Tire | Yes |
| Electric Brakes | Yes |
| 7-Way Plug | Yes |
| Battery *** | Lithium Only - Not Included |
| Fresh Water Tank Capacity | 21 Gallons |
| Refer Size (Option) | 3.3 Cubic Feet |
| A/C w/Heat Pump - BTU's (Option) | 8K Basement A/C w/8K Heat Pump |
| OPTIONS | |
| Roof Rack | 33 lbs. |
| A/C w/Heat Pump | 61 lbs. |
| 12V Lithium Battery | 23 lbs. |
| 32" 12V TV w/Locking Mount | 12 lbs. |
| Rear Awning & Bracket | 17 lbs. |
| 3.3 cu ft 12V Refer w/OH cabinet | 36 lbs. |
| Heavy Duty Fenders | 25 lbs. |

*Tongue Weight includes the following options (Roof Rack, A/C, & Awning Package)

**Roof Rack rated at 100 lbs (45kg) per crossbar - Dynamic Rating

***You *cannot* use a standard wet cell deep cycle battery