



| Specifications                 | 14TH1                       | 14TH2                |
|--------------------------------|-----------------------------|----------------------|
| Dry Weight (No Options)        | 2,368 lbs                   | 2,437 lbs            |
| Tongue Weight (No Water)       | 567 lbs                     |                      |
| Tongue Weight (w/Water)        | 536 lbs                     |                      |
| GVWR                           | 4,400 lbs                   |                      |
| Torsion Axle Rating            | 4,000 lbs                   |                      |
| Overall Length                 | 198-1/4" (16' 6-1/4")       |                      |
| Overall Width                  | 95" (7' 11")                |                      |
| Box Length (Exterior)          | 165-1/2" (13' 9-1/2")       |                      |
| Interior Floor Length          | 136" (11' 4")               |                      |
| Interior LQ Width              | 69-1/4" (5' 9-1/4")         |                      |
| Interior LQ Height             | 73" (6' 1")                 |                      |
| Interior LQ Height @ A/C       | 71-3/4" (5' 11-3/4")        |                      |
| Ramp Door Opening              | 70-1/2" X 64"               |                      |
| Ramp Door Platform             | 70" X 63"                   |                      |
| Ramp Door Capacity             | 2,500 lbs                   |                      |
| Tip-Out Bunk Size              | 77" X 44" (Roadside)        | 77" X 44" (Curbside) |
| Tip-Out Bunk Capacity          |                             | 1,100 lbs            |
| Overall Height w/Roof Rack     | 110-3/4" (9' 2-3/4")        |                      |
| Overall Height w/A/C           | 107-1/2" (8' 11-1/2")       |                      |
| Overall Height w/Roof Vent)    | 102-1/2" (8' 6-1/2")        |                      |
| Ground Clearance               | 11-1/8"                     |                      |
| Roof Rack Capacity*            | 400 lbs                     |                      |
| Rear Receiver Capacity         | 200 lbs                     |                      |
| Coupler                        | 2-5/16"                     |                      |
| Hitch Ball Height              | 17-1/2"                     |                      |
| Tires                          | ST235/75R15 LRC             |                      |
| Wheels                         | 15" X 6"                    |                      |
| Lug Pattern                    | 6 X 5-1/2"                  |                      |
| Spare Tire                     | Yes                         |                      |
| Electric Brakes                | Yes                         |                      |
| 7-Way Plug                     | Yes                         |                      |
| Battery **                     | Lithium Only - Not Included |                      |
| Fresh Water Tank Capacity      | 26 Gallons                  |                      |
| Refer Size - Inside Kitchen    | 3.3 Cubic Feet              |                      |
| Furnace Size                   | 18,000 BTU                  |                      |
| Roof Top A/C (Cooling/Heating) | 13,500/13,200 BTU           |                      |

\*Roof Rack rated at 100 lbs (45kg) per crossbar - Dynamic Rating

\*\*You *cannot* use a standard wet cell deep cycle battery