



Specifications

16FB

Dry Weight (No Options)	2,998 lbs
Tongue Weight (No Water)	557 lbs
GVWR	4,400 lbs
Torsion Axle Rating	4,000 lbs
Overall Length	233" (19' 5")
Overall Width	95" (7' 11")
Box Length (Exterior)	190" (15' 10")
Interior LQ Length	81" (6' 9")
Interior LQ Width	69-1/4" (5' 9-1/4")
Interior LQ Height	73" (6' 1")
Interior Bunk Length	80" (6' 8")
Interior Bunk Height	48" (4')
Interior Bathroom Width	26-3/4" (2' 2-3/4")
Interior Bathroom Height	72-1/2" (6' 1/2")
Interior Bathroom Height to Skylight	77-1/2" (6' 5-1/2")
Interior Bathroom Length	47" (3' 11")
Shower Pan Dimensions	27" X 36"
Dinette Bunk Dimensions	69" X 32"
Overall Height w/Roof Rack	109-3/4" (9' 1/2")
Overall Height w/A/C	107-1/2" (8' 11-1/2")
Overall Height w/Roof Vent)	102-1/2" (8' 6-1/2")
Ground Clearance	11-1/8"
Roof Rack Capacity*	500 lbs
Rear Receiver Capacity	200 lbs
Coupler	2-5/16"
Hitch Ball Height	17-1/2"
Tires	ST235/75R15 LRC
Wheels	15" X 6"
Lug Pattern	6 X 5-1/5"
Spare Tire	Yes
Electric Brakes	Yes
7-Way Plug	Yes
Battery **	Lithium Only - Not Included
Fresh Water Tank Capacity	54 Gallons
Refer Size - Inside Kitchen	4.5 Cubic Feet
Refer Size - Exterior Kitchen	1.7 Cubic Feet
Furnace Size	18,000 BTU
Roof Top A/C (Cooling/Heating)	13,500/13,200 BTU

*Roof Rack rated at 100 lbs (45kg) per crossbar - Dynamic Rating

**You *cannot* use a standard wet cell deep cycle battery