



Specifications	20TH1	20TH2
Dry Weight (No Options)	3,998 lbs	4,067 lbs
Tongue Weight (No Water)	866 lbs	
Tongue Weight (w/Water)	816 lbs	
GVWR	7,000 lbs	
Torsion Axle Rating	Tandem 3,500 lbs	
Overall Length	287" (23' 11")	
Overall Width	103-1/2" (8' 7-1/2")	
Box Length (Exterior)	237-3/8" (19' 9-3/8")	
Interior Floor Length	208" (17' 4")	
Interior LQ Width	82" (6' 10")	
Interior LQ Height	81-1/2" (6' 9-1/2")	
Interior LQ Height @ A/C	80-1/4" (6' 8-1/4")	
Ramp Door Opening	80-1/4" X 76"	
Ramp Door Platform	75-1/4" X 79-3/4"	
Ramp Door Capacity	2,500 lbs	
Tip-Out Bunk Size	77" X 44" (Roadside)	77" X 44" (Curbside)
Tip-Out Bunk Capacity		1,100 lbs
Overall Height w/Roof Rack	118-3/4" (9' 10-3/4")	
Overall Height w/A/C	116-1/2" (9' 8-1/2")	
Overall Height w/Roof Vent)	111-1/2" (9' 3-1/2")	
Ground Clearance	12-1/2"	
Roof Rack Capacity*	500 lbs	
Rear Receiver Capacity	200 lbs	
Coupler	2-5/16"	
Hitch Ball Height	17-1/2"	
Tires	ST235/75R15 LRC	
Wheels	15" X 6"	
Lug Pattern	5 X 4-1/4"	
Spare Tire	Yes	
Electric Brakes	Yes	
7-Way Plug	Yes	
Battery **	Lithium Only - Not Included	
Fresh Water Tank Capacity	26 Gallons	
Refer Size - Inside Kitchen	3.3 Cubic Feet	
Furnace Size	18,000 BTU	
Roof Top A/C (Cooling/Heating)	13,500/13,200 BTU	

\*Roof Rack rated at 100 lbs (45kg) per crossbar - Dynamic Rating

\*\*You *cannot* use a standard wet cell deep cycle battery